

# SUPPLY OF ARTWORK

## If you're sending us print ready artwork

1. Create your artwork in Adobe Illustrator or CorelDraw at 1/10 scale.
2. All colours to be set to CMYK. RGB or spot colours cannot be used.
3. Ensure all important graphics, logos and text are clear from trim edge.
4. All logos used should be vector artwork. Avoid image based logos.
5. All images to be embedded into artwork as CMYK tif files at a minimum of 300dpi and a maximum of 600dpi.
6. Avoid using complex or multiple effects text or graphics. If effects are used, flatten layers before saving as a print ready pdf.
7. Ensure all text is converted to outlines.
8. Please provide bleed as per below:

### **Standard sized full mesh rolls require bleed top and bottom only -**

*Banner Mesh with hemming and eyelets - 50m roll x 1.6m = 5000 x 164mm*

*Banner Mesh with hemming, rope & eyelets - 50m rolls x 1.6m = 5000 x 167mm*

### **Custom sized orders -**

*Banner Mesh with eyelets. Finished size plus 20mm bleed on all edges.*

*Banner Mesh with rope/rope & eyelets. Finished size plus 35mm on all edges.*

*PVC with hemming and eyelets. Finished size plus 25mm on all edges.*

*PVC with rope/rope & eyelets. Finished size plus 35mm bleed on all edges.*

*PVC with kedar edge. Supply art at the finished size. No bleed required.*

## If you require us to create your artwork

1. Supply all your logos as vector files in pdf or eps formats. Avoid image based logos wherever possible.
2. Supply all images at 300dpi - 600dpi at the largest file size you have, but no smaller than 10% of the desired print size at 300dpi.
3. Provide all to be included in your design via email or Word document.
4. Supply a copy of any corporate fonts and CMYK colours required.